

<Reference 3>

Japan Utility Model Application

Publication No. 58-098348, U

Date of Publication: July 4, 1983

Applicant: Hokoku Plastics MFG. Co., Ltd.

## HOLDING STRUCTURE FOR PACKING IN CAP

This invention relates to a holding structure for a packing in a resin cap. The holding structure comprises a circular packing provided in an outer periphery of an inner surface top of the resin cap which is threadedly engaged with a mouth of a container body so as to seal by the packing. The cap comprises a circular protrusion engaging portion protruding radially inwardly to the top of the inner periphery surface thereof and a holding portion protruding downwardly at the outer periphery of the inner surface top. The packing is inserted between the holding portion and inner surface of the cap such that the packing is retained with the use of the protrusion engaging portion and a retaining portion folded outwardly in a radial direction of the lower end of the holding portion.

## ⑪ 公開実用新案公報 (U)

昭58-98348

⑤Int. Cl.<sup>3</sup>  
B 65 D 53/02  
51/24

識別記号 庁内整理番号  
6564-3E  
6564-3E

④公開 昭和58年(1983)7月4日

審査請求 有

(全 1 頁)

## ⑥キヤップにおけるバッキング保持構造

東大阪市柏田本町15番8号 豊國樹脂工業株式会社内

②実願 昭56-194589

⑦出願人 豊國樹脂工業株式会社

②出願 昭56(1981)12月23日

東大阪市柏田本町15番8号

②考案者 德原秀嗣

⑧代理人 弁理士 安田敏雄

## ③実用新案登録請求の範囲

樹脂製キヤップ1内面頂部9外周に環状バッキン  
グ11が設けられ、前記キヤップ1を容器本体  
4の口部に螺着して前記バッキング11でシール  
するものにおいて、前記キヤップ1はその内面  
上部に径方向内方に突設された環状の突出係合部  
8と、内面頂部9外周部で下方に突設された保持  
部10とが備えられ、前記バッキング11が保持  
部10とキヤップ1内周面2との間に嵌入され、  
前記保持部10下端部の径方向外方に折曲形成さ


れた拔止部12と前記突出係合部8とで前記バッ  
キング11が拔止め保持されたことを特徴とする  
キヤップにおけるバッキング保持構造。

## 図面の簡単な説明


第1図は本考案の実施例を示す正面断面図、第  
2図は第1図の要部拡大図、第3図は他の実施例  
を示す要部拡大図である。

1…キヤップ、2…内周面、4…容器本体、5  
…口部、8…突出係合部、9…内面頂部、10…  
保持部、11…バッキング、12…拔止部。

第2図



第1図



第3図

